



特點 Features :

1. 採用水壓系統，可依鞋款調整壓力，平均拉力可達 7 kg/cm²。
Using hydraulic system, pressure can be adjusted according to the shoe style, the average pulling force can reach 7 kg/cm².
2. 勿需另外制作傳統式壓底模，降低模具費，沒有環保問題，對鞋面、中底、大底、孔位修邊非常迅速。
It is unnecessary to make a traditional press-bottom mold, reducing the mold cost and there is no environmental protection problem.
3. 符合歐規 CE 安全標準、具有安全傳感器、安全開關、緊急按鈕等，三重安全裝置，杜絕安全隱患。
It meets European CE safety standards, safety sensors, safety switches, emergency buttons, etc., triple safety device eliminates safety hazards.
4. 一次可完成三種壓著，可減少多機多人浪費。
Three kinds of pressing can be completed at one time, which can reduce waste of multi-machine and multi-person.

技術參數 Technical Parameter :

壓力範圍 Pressure Range : 0-25 kg / cm²
工作範圍 Working Range : 450 mm
生產效率 Product efficiency : 2400 / 8h
電機功率 Power : 3 hp
工 作 油 Work Oil : 水溶性工作油 Hydrolysis oil

機器尺寸 Machine Size : 1000 x 920 x 1630 mm
包裝尺寸 Packing Size : 1120 x 1100 x 1850 mm
淨重 N.W. : 1400 kg
毛重 G.W. : 1450 kg